

222

ITEM	DESCRIPTION	PART NO. OR EQUIVALENT
1	65" LCD Monitor; 64-17/32" Diagonal; Full 1080x1920 High Definition Resolution; Brightness: 420 nit; Inputs: HDMI (AV: 1080p/50Hz, 1080p/60Hz), DVI-D (24-pin), Analog RGB (15-pin Mini D-sub), 5-BNC (Selectable RGB analog or Component Video), S-Video (4-pin DIN), Composite Video (BNC), Stereo Audio for PC (3.5mm Stereo Mini-Jack), Stereo Audio for AV (RCA pin L/R), LAN (RJ-45), and RS-232C In/Out Serial Port (9-pin D-sub); Outputs: DVI-D Loop-through (24-pin), Stereo Audio Line-out (RCA pin L/R), and Stereo Audio (7W/channel) Speaker Terminals; 16.7 Million Colors (Full Color); Contrast Ratio 2000:1; Aspect Ratio 16:9; Pixel Pitch 0.744mmx0.744mm; Viewing Angle 176 degrees Hor/176 degrees Vert; Response Time 6 ms; Dimensions 61.9"Wx36.3"Hx5.0"D; Weight 137 lbs.	PN-S655
2	42" LCD Monitor; 42" Diagonal; 1366x768 Resolution; Brightness: 500 cd/m squared; Inputs: DVI-D (24-pin), Analog RGB (15-pin D-sub), RGBHV (5 BNC), Composite (Shared RCA and BNC), S-Video (4-pin DIN), Component Y, Cb/Pb, Cr/Pr (BNC), Stereo Audio (L/R) x 2 (RCA), Stereo Audio (3.5mm Mini-Jack), External Speaker Jacks; Outputs: RGB, Composite, Audio, 7W Speaker Terminals; Contrast Ratio 800:1; Aspect Ratio 16:9; Pixel Pitch 0.681mm; Viewing Angle 178 degrees Vert/178 degrees Hor; Response Time 9 ms; Dimensions 40.3"Wx24.2"Hx5.2"D; Weight 45.2 lbs.	LCD4215
3	Flat Panel Lockable Tilt Wall Mount (Up to 65" or 200 lbs.); Depth from Wall: 1.54"; Overall Dimensions: 18.38"Hx26"Wx1.54"D; Tilt: 0-15 degrees; Mounts to Studs: 16", 20" and 24" On-center; Color: Black; Weight Capacity: 200 lbs.	PRO2244
4	Flat Panel Dual Swing Arm Wall Mount (Up to 71" or 200 lbs.); Depth from Wall: 3.4"; Extension from Wall: 37"; Dimensions: 22.04"Hx39.5"Wx3.4"D; Tilt/Roll: +5 degrees, -17 degrees/+ or - 2.5 degrees; Height Adjustment: 1"; Mounts on Studs: 15" On-Center with 4.5" Left/right Lateral Shift; Color: Black; Weight Capacity: 200 lbs.; Channel Size Each Arm: 5/8" Wide	PDR2241B
5	Deluxe Mobile Rack, 21 Rack Units; Furniture Grade Laminates; EIA Compliant, Threaded 21RU Rack Rails; Top and Bottom Cable Access Grommets; Locking Tempered Glass Front Door; Locking and Removable Vented Rear Panel; Premium Casters; Ships Fully Assembled; Dimensions: 23"Wx27"Dx42"H; Medium Cherry Color	AV21RU-MC
6	Modular Multi-Plane Matrix Switcher, SMX 400 Frame, 4U/8-Slot; Rack-mountable; RS-232 or RS-422 (9-pin Female D Connector) Serial Host Control Port; Dimension: 7"Hx17"Wx12"D	60-856-01
7	Wideband VGA Matrix Switcher Boards, 16x16 Wideband (15-pin HD), 4 Slots; Gain:Unity; Bandwidth: 300 MHz; Crosstalk: -55 dB @ 10 MHz; Switching Speed: 200 ms (max.); Video Input and Output Signal Type: VGA-QXGA, RGBHV, RGBS, RGSB, RsGsB; Video Input and Output Impedance: 75 Ohms; Video Input and Sync Horizontal Frequency: 15 kHz to 150 kHz; Video Input and Sync Vertical Frequency: 30 Hz to 150 Hz; Sync Input Impedance: 510 Ohms; Sync Output Impedance: 75 Ohms; Max Sync Propagation Delay: 30 ns; Max Sync Rise/Fall Time: 4 ns	70-596-04
8	S-Video Matrix Switcher Boards, 16x16 S-Video (DIN), 2 Slots; Gain: Unity; Bandwidth: 150 MHz; Crosstalk: -50 dB @ 5 MHz; Switching Speed: 100 ms (max); Video Input and Output Impedance: 75 Ohms; Video Input and Output Nominal Level: 1 Vp-p for Y of S-Video and 0.3 Vp-p for C of S-Video	70-592-04
9	Stereo Audio Matrix Switcher Boards, 16x16 Stereo Audio, 2 Slot; Gain:Unbalanced Output -6 dB, Balanced Output 0 dB; Frequency Response: 20 Hz to 20 kHz; S/N: >90 dB at Maximum Output; Crosstalk: <-80 dB @ 1KHz; Stereo Channel Separation: >80 dB @ 1 kHz; CMRR: >75 dB @ 20 Hz to 20 kHz; Input and Output Connectors: 3.5 mm Captive Screw Connector, 5 Pole; Input Impedance: >10k Ohms Unbalanced/Balanced, DC Coupled; Input Nominal Level: 0 dBu; Maximum Level: +19.5 dBu; Input Gain Adjustment: -18 dB to +24 dB, Adjustable per Input, Default=0 dB; Output Impedance: 50 Ohms Unbalanced, 100 Ohms Balanced; Maximum Output Level (Hi-Z): >+21 dBu; Maximum Output Level (600 Ohm): >+15 dBm; Volume Control Range: -85 dB to 0 dB	70-599-04

10	NetLinX Integrated Controller, NI-4100; 8 IR/Serial Output Ports; 8 Digital I/O Channels; 8 Relay Channels; 7 Configurable RS-232/RS-422/RS-485 Serial Ports; 1 Ethernet 10/100 Port; 1 AxLink Bus Connector; 2 ICSNet Ports; 1 ICSHub Port; 4 NetLinX Control Card Expansion Slots that Support all NXC Control Cards; 404 MIPS Processor Speed; 64 MB RAM; 128 MB Compact Flash; 1 MB Non-Volatile Memory; Device Discovery Enabled; Power 900mA @ 12 VDC; Dimensions: 5-3/16"Hx17"Wx9-5/16"D; Weight: 9.15 lbs.	FG2105-06
11	Volume Card, 4 Channels, NXC-VOL4; Four Line-level Audio Volume Channels and Front-panel Feedback; Supports Balanced and Unbalanced Applications; Four Status LED's; Jumpers Allow Selection of Unity Gain, Gain from -10 dB Input to +4 dB Output, or Attenuate from +4 dB Input to -10 dB Output; 3.5mm Captive-screw terminals; Frequency Response of 15 Hz-25 kHz; THD less than .005 at Nominal Output Level; IMD less than .01 at Nominal Output Level; S/N Ratio Greater than 100 dB; Crosstalk less than 80 dB; Logarithmic Attenuation Range of 95 dB	FG2024
12	15" Modero Table Top Touch Panel w/RGB, NXT-1500VG RGB KIT; Analog Stereo Audio and Composite Video Inputs; RGB or Component Input via NXA-AVB/RGB; Streaming MPEG-2 Digital Video and Audio; Network Video - Motion JPEG; Video Formats: NTSC, PAL, and SECAM; 15" Active-matrix Display; Aspect Ratio: 4:3; Brightness: 400 cd/m squared; Contrast Ratio: 300:1; Screen Resolution: 1024x768 Pixels; Display Colors: 15 Million Colors (24-bit Color Depth); 8-bit Alpha Channel Transparency; Motion Sensor; Light Sensor; 256 MB SDRAM/128 MB CompactFlash Memory; Wired 10/100 Ethernet; Constant Current Draw: 3.7A @ 12VDC; Startup Current Draw: 5.5A @ 12VDC; Dimensions: 7-1/2"Hx15"Wx11-1/2"D; Weight: 17.15 lbs.	FG2252-61RGB
13	Modero Viewpoint 8.4" Wireless Touch Panel, MVP-8400; 8.4" Color Active-matrix TFT; Aspect Ratio: 4:3; Brightness: 180 cd/m squared; Contrast Ratio: 350:1; Screen Resolution: 800x600 Pixels; Display Colors: 256K (18-bit Color Depth); Anti-glare Overlay; Built-in Speakers (2) and Microphone; 64 MB SDRAM; 64 MB CompactFlash; Operates with 1 or 2 MVP-BP Rechargeable Battery Packs; 802.11 Wireless Ethernet; 38kHz and 455kHz Infrared; Mini-USB for Programming File Transfer; Docking Station Interconnect; Coaxial Barrel Connector for Power Supply; 9 Programmable Buttons; Dimensions: 7.17"Hx10.47"Wx1.34"D; Weight: 2.65 lbs.	FG5965-05
14	Table Top Docking Station for 8.4" Modero Viewpoint Touch Panel, MVP-TDS; Electromagnet to Secure the Touch Panel to the Docking Station; Release Pushbutton to Disengage the Electromagnet and Allow Removal of the Touch Panel from the Docking Station; Two LEDs to Indicate Battery-charging Status and Communications; Two Type A USB Ports for Keyboard and Mouse; Power Supply Jack, 13.5 VDC, 6mm Coaxial Male; Dimensions: 7-6/16"Hx7-1/16"Wx9-13/16"D; Weight: 4.57 lbs.	FG5965-10
15	12VDC Power Supply, PSN6.5; 13.5 VDC at 6.5A on Three 3.5 mm Power Connectors; Switching Regulated, Overload Protected; AC Power Input: 110 VAC, U.S. Power Cord; Dimensions: 1-1/2"Hx5-1/2"Wx9-1/4"D; Weight: 1.85 lbs.	FG423-41
16	Wall Mount IR Receiver, MIO-IRRX-BG; Works with AMX IR-format 38 kHz or 455 kHz Wireless Transmitters; Fits in most US-style Single Gang Enclosures; Single Style Beige Faceplate; 4 Pin 3.5mm Phoenix AxLink Connector; Power: 12VDC, 15mA; Dimensions: 4-1/2"Hx2-11/16"Wx9/16"D; Weight: 0.15 lbs.	FG5797-01BG
17	Video Switch; Supports up to Six High Definition Camera Inputs; Supports HD Cameras from Third Party Vendors Through an Analog Component Interface; Enables Support for Standards Based Optical and Electrical Cable Extension Solutions; 4 DVI-D Inputs; 2 Analog Component Inputs; 1 THSI Output (to Tandberg CODEC); 1 HDMI Output; 3 Serial Ports for Camera Control and Direct Control System Control; Rackmountable; Includes Rack Ears, Power Supply, 2 THSI Cables, Visca Control Cable, Power Supply for HD Camera, HDMI-DVI Video Cable	116460
18	Customer Core Service for Video Switch; Provides Software Upgrades, Technical Phone or Email Support, and Replacement Parts for 1 Year	116460V31D
19	Power Supply for Tandberg Precision High Definition Camera	1156231

	DVD/VCR Recorder; Multi-Format Playback (Playable Disc Type): DVD, DVD-RAM, DVD-R/-RW, DVD-R(DL), +R/+R(DL)/+RW, CD, CD-R/RW; Recordable Disc Type: DVD-RAM, DVD-R, DVD-R(DL), DVD-RW, +R, +R(DL), +RW; Dolby Digital 2-channel Audio Recording; 2 Analog Audio (2 Ch) Line Inputs; 2 Video Inputs; 1 DVI Input; 1 S-Video Input; Built-in SD Card Slot; 2 Audio (2 Ch) Outputs (One is DVD Priority); Component Video Output (DVD Priority); S-Video Output (DVD Priority); Digital Audio Output, 2 Video Outputs (One is DVD Priority); HDMI Output (DVD Priority); TV Channel Analog/Digital 2-69 Channels; CATV Channel Analog/Digital 1-135 Channels; Dimensions: 3-5/16"Hx16-15/16"Wx13-5/8"D; Weight: 11.9 lbs.	DMR-EZ48VK
20	CPM101 One-Gang, Four-Space Mounting Frame for up to Four Mini Architectural Adapter Plates (MAAP), White; Dimensions: 4.5"x2.75"x0.1"	60-583-21
21	One S-Video Female to Female Barrel MAAP, White, Size: Single Space	70-287-22
22	One HDMI Female to Female Barrel MAAP, White, Size: Single Space	70-617-03
23	Two Mini XLR 3-Pin Male to Solder Cups MAAP, White, Size: Single Space	70-297-23
24	One 1/4" Stereo Phone Female to Solder Tabs MAAP, White, Size: Single Space	70-295-21
25	One 15-Pin HD Female to Five BNC on 4" Pigtails MAAP, White, Size: Single Space	70-309-24
26	One 15-Pin HD Female to Female Gender Changer MAAP, White, Size: Single Space	70-309-21
27	One 9-Pin D Female to Female Gender Changer MAAP, White, Size: Single Space	70-310-21
28	One RJ-45 Female to Female Barrel - Data MAAP, White, Size: Single Space	70-314-23
29	Blank Plate-Single MAAP, White, Size: Single Space	70-315-21
30	MHR-2 SVM-M/6 Male to Male 4-Pin Mini DIN S-Video Cable, 6 ft.	26-316-02
31	MHR-2 SVM-M/12 Male to Male 4-Pin Mini DIN S-Video Cable, 12 ft.	26-316-03
32	MHR-2 SVM-M/30 Male to Male 4-Pin Mini DIN S-Video Cable, 30 ft.	26-316-04
33	MHR-2 SVM-M/50 Male to Male 4-Pin Mini DIN S-Video Cable, 50 ft.	26-316-05
34	MHR-2 SVM-M/75 Male to Male 4-Pin Mini DIN S-Video Cable, 75 ft.	26-316-06
35	MVGA M-M/3 Male to Male Micro VGA Cable, 3 ft.,	26-567-01
36	MVGA M-M/12 Male to Male Micro VGA Cable, 12 ft.	26-567-03
37	MVGA M-M/25 Male to Male Micro VGA Cable, 25 ft.	26-567-04
38	HDMI M-DVI-D M/12 High Performance HDMI Male to DVI-D Male Cable, 12 ft.	26-614-03
39	HDMI M-M/35 High Performance HDMI Male to Male Cable, 35 ft.	26-613-05
40	HDMI M-M/50 High Performance HDMI Male to Male Cable, 50 ft.	26-613-06
41	MHR-5/500 Five Conductor MHR - Mini High Resolution Cable, 26 AWG, Nominal Core Overall Diameter 0.076", Shielding Materials: Aluminum Foil (100%), Nominal Overall Diameter 0.357", Nominal Impedance 75 Ohms, Nominal Capacitance 16.7 pF/ft	22-020-02
42	RSB 129 1U 9.5" Deep Basic Rack Shelf, Black	60-604-01
43		